Contribution ID: 95 Type: Oral or Poster

LLRF System Considerations for a Compact, Commercial C-band Accelerator using the AMD Xilinx RF-SoC

Wednesday, October 25, 2023 3:06 PM (4 minutes)

A C-band klystron is being developed to provide 600 kW peak power to a fully integrated compact linear accelerator system. The design of this high-power RF source was centered on minimizing weight and volume. In doing so, a novel periodic permanent magnet focusing circuit was developed alongside a compact RF circuit to achieve > 50% efficiency in simulation. Fabrication of this system is underway and high-power tests will be performed.

This material is based upon work supported by the Defense Advanced Research Projects Agency under Contract Numbers 140D0423C0006 and 140D0423C0007.

Keyword

Normal conducting, compact, c-band, AMD Xilinx RF-SoC, embedded, sbc

Primary authors: EDELEN, Jonathan (RadiaSoft LLC); EINSTEIN-CURTIS, Joshua (RadiaSoft LLC)

Co-authors: SMIRNOV, Alexander (RadiaBeam Technologies, LLC.); DIEGO, Amiari (RadiaBeam Technologies, LLC.); HONG, Bo (SLAC National Accelerator Laboratory); LIU, Chao (SLAC National Accelerator Laboratory); NANNI, Emilio (SLAC National Accelerator Laboratory); ZUO, Fengrui (SLAC National Accelerator Laboratory); KHALSA, Gurhar (RadiaSoft LLC); MERRICK, Julian (SLAC National Accelerator Laboratory); RUCK-MAN, Larry (SLAC National Accelerator Laboratory); KILPATRICK, Matt; HENDERSON, Morgan (RadiaSoft LLC); AUGUSTSSON, Ronald (RadiaBeam Technologies, LLC.); TANTAWI, Sami (SLAC National Accelerator Laboratory); THIELK, Seiji (RadiaBeam Technologies, LLC.); LI, Zenghai (SLAC National Accelerator Laboratory)

Session Classification: Posters

Track Classification: Hardware